

MX 1150 (T) Stereomicroscope

- Professional ZOOM stereo microscope
- Trinocular tube for photo/video documentation
- Ergonomic design
- New optics with high resolution and large depth of field
- Zoom range: 4–300x
- Widefield eyepieces 10x/22 mm
- Illumination system: transmitted light, incident light
- LED illumination adjustable: incident and transmitted light
- Optical system provided with Anti-Fungus treatment



Specifications

MX 1150 (T) stereomicroscope

General characteristics

Magnification	4–300x
Head	compensation trinocular head, 360° rotatable, 45° inclined, interpupillary distance 50–75 mm
Eyepieces	widefield 10x/22 mm
Microscope body	sturdy metallic base 180x240 mm with supportive rubber feet
ZOOM tube	0.8–5.0x, ZOOM ratio 1:6.3x
Working distance	115 mm
Light source	— adjustable — incident light: LED 12 V, 3 W — transmitted light: LED 12 V, 6 W
Power requirements	built-in, 220 V, 50 Hz
Fuses	250 V, 2 A
Temperature	18–35 °C
Humidity	less than 85 %
Extra lenses	0.5x, 0.75x, 2x

Ordering Information

Description	Code
MX 1150 (T) trinocular stereo microscope, standard set (Option 1)	09.1500.03
MX 1150 (T) trinocular stereo microscope, standard set (Option 2)	09.1500.13
MX 1150 (T) trinocular stereo microscope, standard set (Option 3)	09.1500.23
MX 1150 (T) trinocular stereo microscope, standard set (Option 4)	09.1500.33

We reserve the right to change specification without notice.